

PRODUCT DATASHEET

ECO CLASS DAMP PROOF HLO 1500 66 W 4000 K IP65 TH

ECO CLASS DAMP PROOF HLO GEN 2 | Damp-proof luminaires, classic shape



Areas of application

- Industrial and storage facilities
- Car parks and underpasses
- Garages
- Workshops, assembly lines

Product benefits

- Evenly distributed light
- Energy savings of up to 50 % (compared to luminaires that use fluorescent lamps)
- Easy installation, no tools required for connection
- 5 years guarantee

Product features

- High luminous efficacy: up to 140 lm/W
- Type of protection: IP65
- Beam angle: 120°
- Through-wired (L, N, E)
- Polycarbonate housing



TECHNICAL DATA**Electrical data**

Nominal wattage	66.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Inrush current	30 A
Inrush current time T_{h50}	100 μ s
Max. no. of lum. on circuit break. B16 A	25
Max. no. of lum. on circuit break. C10 A	20
Max. no. of lum. on circuit break. C16 A	32
Power factor λ	≥ 0.90
Total harmonic distortion	20 %
Protection class	II
Operating mode	Integrated LED driver

Photometrical data


Luminous flux	9000 lm
Luminous efficacy	136 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	< 5 sdcn
Luminous intensity	-
Flickering metric (Pst LM)	-
Stroboscope effect metric (SVM)	-
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG1
Beam angle	120 °

LDC typ cone

LDC typ polar

Dimensions & Weight

Length	1510.00 mm
Width	70.50 mm
Height	70.40 mm
Product weight	1790.00 g



Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Polycarbonate (PC)
Cover material	Polycarbonate (PC)
Light emitting surface material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-40...+70 °C
Type of connection	Screwless
Type of protection	IP65
Protection class IK (shock resistance)	IK08
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling / Wall
Application environment	Indoor
LED module replaceable	Not replaceable
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	50000 h ¹⁾
Number of switching cycles	100000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE / EAC / RoHS / REACH
Luminaire with limited surface temperature, "D sign"	Yes

Additional product data



Number of illuminants	-
-----------------------	---

EQUIPMENT / ACCESSORIES





- Mounting material for wall and ceiling installations included

DOWNLOAD DATA

Documents and certificates

	User instruction
	Declarations Of Conformity CE

Photometric and lighting design files

	LDT file (Eulumdat)
	UGR file (UGR table)
	LDC typ cone
	LDC typ polar

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075464025	Folding box 1	1,536 mm x 77 mm x 75 mm	2097.00 g	8.87 dm ³
4058075464032	Shipping box 6	1,560 mm x 250 mm x 165 mm	13921.00 g	64.35 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.