



Industrial Batten



START Batten

The new START Batten is a range of LED battens in four different lengths: 600mm, 1200mm, 1500mm and 1800mm. The range is perfect for lighting large industrial areas such as corridors, warehouses, back of house areas or general purpose spaces. Integrated switches allows to choose between warm white (3000K) and neutral white (4000K)

colour temperatures and to select between two different light levels. 4000K version delivers up to 9200lm (luminaire lumen output), and up to 152lm/W (total system efficacy). The range offers ease of installation through the 2-part housing push-in design.

START Batten



Features


- Range of LED battens in four different lengths: 600mm, 1200mm, 1500mm and 1800mm
- Perfect choice for lighting large industrial areas such as corridors, warehouses, back of house areas or general purpose spaces
- Integrated switch allows to choose between warm white (3000K) and neutral white (4000K) colour temperatures, CRI>80, SDCM<3
- Easy selection between two different light output levels by using the integrated switch (excluding the DALI versions)
- DALI versions
- Dedicated corridor versions with microwave presence sensor
- Optional simple on-off Microwave KIT is available separately that can be easily added to the luminaires
- Emergency KIT is available separately that can be easily added to the luminaires (3 hours self test emergency), excluding to the 600mm length
- RAL9016 - Traffic white housing
- IK08 impact protection
- Ease of installation through 2-part housing push-in design
- End cap incorporates 20mm conduit knock out
- Suitable for direct fix and suspension
- Loop in Loop out terminal block in the middle of the product
- BESA box connection possibility standard on product
- Lifespan at least 100.000 hrs (L70:B50)
- 5 years warranty

Product information

Code	Description	System Power (W)	Fixture lumen (lm)	Efficacy (lm/W)	Colour temperature (K)	Control Technology	Lifespan (L70:B50)	Length (mm)
Standard (Multipower/DualTone)								
0048977	START Batten 600 1600/3000 830/840	12 / 21.5	1525 - 3000	127 - 140	3000 / 4000	Non-dimmable	120,000	600
0048978	START Batten 1200 3000/5000 830/840	20.5 / 35.5	2800 - 5000	135 - 144	3000 / 4000	Non-dimmable	100,000	1200
0048979	START Batten 1500 4000/7000 830/840	28 / 52	3900 - 7300	135 - 146	3000 / 4000	Non-dimmable	100,000	1500
0048980	START Batten 1800 5000/9000 830/840	33 / 68	4550 - 9200	124 - 152	3000 / 4000	Non-dimmable	120,000	1800
Microwave Corridor								
0048981	START Batten 1200 3000/5000 MWC 830/840	20.5 / 35.5	2800 - 5000	135 - 144	3000 / 4000	Non-dimmable	100,000	1200
0048982	START Batten 1500 4000/7000 MWC 830/840	28 / 52	3900 - 7300	135 - 146	3000 / 4000	Non-dimmable	100,000	1500
DALI								
0048983	START Batten 1200 5000 DALI 830/840	36.5	4800 / 4850	132 / 133	3000 / 4000	DALI-2	120,000	1200
0048984	START Batten 1500 7000 DALI 830/840	51.5	6700 / 7100	130 / 138	3000 / 4000	DALI-2	120,000	1500
0048985	START Batten 1800 9000 DALI 830/840	65	8700 / 8900	134 / 137	3000 / 4000	DALI-2	120,000	1800

Code	Description
Accessories	
0048986	START Batten ON/OFF MW Sensor KIT
0048987	START Batten Self Test EM KIT
0048988	START Batten Suspension Set

Photometric Data



Dimensions (mm)




START Batten 600



START Batten 1200



START Batten 1500



START Batten 1800

Additional Images



sylvania-lighting.com

A Feilo Sylvania Company

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this publication, specifications and performance data are constantly changing. Current details should therefore be checked with Feilo Sylvania International Group Kft.
Copyright Feilo Sylvania International Group Kft. Limited January 2023

T:
Email: